

Head Office

Unit 12, 8 Leighton Place
Hornsby
NSW, 2077
Australia

Firefly Office

P.O BOX 52
Laidley
QLD, 4341
Australia

Contact details

Phone: (07) 5411 4209
Mobile: 0400 966 899
Email: trevor@tbafirefly.com.au

MATERIAL DESCRIPTION

Phoenix EA is a lightweight, waterproof sarking, foil faced on one side.

CERTIFICATION

Tested for both vertical and horizontal applications

AS1530.4

BRANZ Report Number FAR2701

AS1530.2-1993 Flammability Test

AWTA Report Number 7-576926-CN

AS4200.1-1994 Clause 6.1.3

AS1301.448s -1991

AS/NZS 4200.1-1994 Table 1 (Extra Heavy Duty)

Number: 7-577747-CN

AS/NZS4201.4-1994 (PASS)

AS/NZS4200.1-1994 CLAUSE 6-4 (High)

AWTA Report

*Full compliance to AS3959-2009 Extra Heavy
Duty Sarking for BAL-12.5<BAL40*

UNIT OF MEASURE ROLL

SIZE 25m x 1m = 25m²

WEIGHT

560g per m2 THICKNESS 1mm

FRL- /90/-

APPLICATIONS

Phoenix EA extra heavy duty sarking is used to wrap the outside of timber or steel roof and wall frames to provide superior protection against mild to severe ember attack during bush fires. In addition to its flammability index of 1 it has a Fire Rating Level of -/90/- when tested to AS1530.4 (Method for fire tests on building materials, components and structures).

PHOENIX EA SARKING



Sarking Under Eave Protection



Starting Roof Wrap



Completed Roof Sark